



## Truly hybrid expansion

### Ultimate wireless flexibility for any PCX control panel

Add any wireless Pyronix peripheral to any PCX control panel to meet any installation needs! Select from the entire Pyronix range to easily cover extensions, outbuildings and much more to new and existing systems. If the property is expanding, so can its security.

Complies with EN50131-1

# PCX-RIX32-WE WIRELESS EXPANDER



Deliver the inputs the installation needs with the ability to add 32 wireless inputs, 32 wireless keyfobs & 2 wireless bells

This provides the ultimate flexibility for any PCX control panel. If it is difficult to reach, needs a less invasive installation and requires more detectors, contacts and safety sensors, the PCX-RIX32-WE has it covered.

Beat the burglar with tamper protection

This ensures that maximum security is maintained against accidental or malicious tampering of the system, providing added peace of mind that the system is secure.

Faster installation, less invasion, upsell opportunities & the same superior security with two-way wireless technology

- **No wires, no fuss**

As the system is fully wireless there is no need to run wiring by lifting floorboards or moving furniture, saving you time and money.

- **One-Push-To-Learn**

A feature in all Enforcer wireless devices that means learning them onto the system can be done in seconds. A simple one button learning feature for easy installation.

Partcode	PCX-RIX32-WE
<b>Type of Module</b>	
Wired input expander module	×
Two-way wireless expander module	✓
Output expander module	×
<b>Key Features</b>	
Wired inputs (NC/DEOL/3-EOL)	×
Inertia and roller shutter sensors support	×
Output support	×
Two-way wireless inputs	32
Two-way wireless keyfobs	32
Two-way wireless sirens	2
Housing with tamper protection	Plastic
Integrated power supply	×
Power input	9 - 15 DC
<b>Other Details</b>	
Operating   storage temperature	-10°C to +50°C   -20°C to +60°C
Weight	315g
Dimensions	173 x 125 x 32mm
Warranty	2 years
<b>Certifications</b>	
Electrical conformity	CE
EN50131	Grade 2
Environmental class	II

- **Signal Strength Indicators (SSI)**

SSI in all Enforcer wireless devices allow them to be optimally positioned during installation, without the need to refer back to the panel.

- **Instant Two-Way Device Control (ITDC)**

This enables the instant wake up and instant sleep of each Enforcer wireless device on the system to preserve battery power and operability, whilst maintaining security.

Meet the required security standard with Grading options

The PCX-RIX32-WE is Grade 2 for the superior security the installation needs.